

The IBM System Storage DS3400 leads the way for organizations to take advantage of consolidating and sharing data within a direct-attach or SAN solution



IBM System Storage DS3400



Highlights

- **4 Gbps Fibre Channel (FC) interface technology**
- **Easy to deploy and manage with the DS3000 Storage Manager**
- **Combination of 12 SAS or SATA 3.5" drives per enclosure**
- **Scalable to 3.6 TB of storage capacity with 300 GB hot-swappable SAS disks or 12.0 TB with 1.0 TB hot-swappable SATA disks in the first enclosure**
- **Expandable by attaching up to three EXP3000s, a total of 14.4 TB of storage capacity with 300 GB SAS or up to 48.0 TB with 1.0 TB SATA**
- **Flexible for use with IBM System x™, IBM System p™ and BladeCenter® servers**
- **Affordable for the small and medium business budgets**
- **Telco model supports -48 V dc power supplies**
- **NEBS and ETSI compliance for AC and DC models**
- **Direct-attach or SAN solution**

As a business matures, so does the amount of data and the value of the data that it holds within the organization. If the data is distributed across servers and individual storage systems, the business will face increased cost and complexity along with the accompanying business risks.

The IBM System Storage™ DS3400 leads the way for these organizations to take advantage of consolidating and sharing this data within a direct-attach or SAN solution. With SAS and SATA drive Internix support, the DS3400 can be optimized with the right workload demand utilizing the appropriate drive technology. The DS3400 offers the opportunity to meet the demands of data expansion, data availability and flexibility in a simple, affordable disk system.

Select configurations of the DS3400 are part of the IBM Express Portfolio™, designed and priced to meet the needs of mid-sized businesses. The Express

models combine the DS3400 storage system with the FC cables and SFP transceivers to help you get started with storage quickly.

Easy to deploy and manage

Most small business IT departments have one administrator or a part-time administrator and limited time to spend on data management. The DS3400 can be easily installed without extensive knowledge or effort.

The DS3000 Storage Manager software was designed for simple implementation by an unseasoned administrator. The task-oriented management interface of the DS3000 Storage Manager presents tasks to the administrator first, then asks on which object to perform the task. This contrasts with an object-oriented interface of a typical system in which the object is selected before the task, which requires a greater depth of storage networking expertise. The DS3000 Storage Manager approach enables even non-storage administrators to quickly set up and deploy the storage solution. The management application's task-oriented interface removes the resistance that many organizations have with their limited in-house expertise.

Tiered storage solution

Tiered storage is the assignment of different categories of data to different types of drives in order to reduce total storage cost. A key attribute of the DS3000 series of disk systems is the integration of SAS and SATA technologies within a single enclosure. By accommodating high-access and near-line data within a single enclosure, the right application with the appropriate drive technology is accomplished. This simplifies purchasing and storage deployment with nearline applications using inexpensive SATA drives and highly-utilized applications deploying SAS drives. Tiered storage solutions help match your IT investment with your information value to maximize the return on your IT investments.

Expand with multiple EXP3000s

The scalability of the DS3400 enables IT managers to respond to a constantly changing storage environment. By starting small, the DS3400 enables users to make additional investments in their infrastructure when data growth necessitates; thus organizations can

easily increase capacity and storage capabilities with minimal cost and effort. The DS3400 capacity is increased by adding hard disk drives or by expanding the configuration and adding EXP3000 expansion units. Both of these operations can be done without shutting down the DS3400, which means "zero-impact" to your environment and gives the user control of data storage with the ability to expand capacity on an as-needed basis.

Flexible approach to storage

The DS3400 is a comprehensive storage solution for IBM System x, IBM System p, BladeCenter and select third-party servers. This flexibility enables you to break free of server barriers and use a single storage solution in a mixed vendor environment. And because you do not have to sacrifice functionality for affordability, the DS3400 disk storage system can deliver powerful dynamic capabilities that help you protect data. The disk storage system enables copy and disaster recovery features such as FlashCopy® and VolumeCopy that can be enabled when required by your application.

Telco options

The IBM System Storage DS3400 includes a DC powered model that is especially suited for telco industry environments. The IBM System Storage DS3400 Model 42T, a NEBS-3 and ETSI compliant disk system and the IBM System Storage EXP3000

Model 02T storage expansion unit are both designed to be powered from a -48 V dc telco industry-standard power supply.

Priced right for small business

With the functionality and availability features that come standard and a price point that does not strain the

budget, the DS3400 is the simple choice for small and medium businesses. Other storage products require the purchase of expensive options for basic storage configurations. The DS3400 is a solution that comes ready to satisfy the majority of storage needs.

IBM System Storage DS3400 at a glance

| | |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Models | 1726-41X—single controller 1726-42X—dual controller 1726-42T—dual controller Telco 1726-41E—single controller Express 1726-42E—dual controller Express |
| RAID controller | Dual active |
| Cache per controller | 512 MB battery-backed cache with 1 GB upgrade option |
| Host interface | Two host ports per controller, Fibre Channel (FC) 4 Gbps auto-sensing 1 Gbps/2 Gbps |
| Drive interface | Serial Attached SCSI (SAS) |
| Supported drives | Supports 3 Gbps SAS: 73 GB, 146 GB and 300 GB SAS drives at 10,000 rpm and 36 GB, 73 GB, 146 GB and 300 GB SAS drives at 15,000 rpm speeds 3 Gbps SATA: 500 GB, 750 GB and 1.0 TB SATA drives at 7,200 rpm speed |
| RAID levels | RAID 0, -1, -3, -5, -10 |
| Storage partitions | 4, 16 |
| Maximum drives supported | 48 SAS or SATA drives (using three EXP3000 Expansion Units) |
| Fans and power supplies | Dual-redundant, hot-swappable |
| Rack support | 19" industry-standard rack |
| Management software | IBM System Storage DS3000 Storage Manager |
| SAN support | Supported IBM FC switches |
| Warranty¹ | Three-year parts and labor warranty |
| Size | Height: 8.7 cm (3.4 in.) Depth: 55.0 cm (21.6 in.) Width: 44.7 cm (17.6 in.) Weight: approximately 17.2 kg (38.0 lb) for a standard unit; when fully configured, 29.2 kg (64.5 lb) |



IBM System Storage DS3400 at a glance

| | |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Environment | Air temperature: – DS3400 on: 10° to 35°C (50.0° to 95°F); altitude: 30.5 (100 ft) below to 3000 m (9840 ft) above sea level; temperature change: 10°C (18°F) per hour – DS3400 off: 10° to 50°C (14.0° to 120.0°F); maximum altitude: 3000 m (9840 ft); temperature change: 15°C (27.0°F) per hour Humidity: – DS3400 on: 20 to 80% – DS3400 off: 10 to 90% – Maximum dew point: 26°C (79°F) – Maximum humidity gradient: 10% per hour |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

| | |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Heat output | Approximate heat output in British thermal units (Btu) per hour: – Minimum configuration: 205 Btu (60 watts) – Maximum configuration 1235 Btu (361 watts) |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|

| | |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supported systems | For a list of currently supported servers, operating systems, host bus adapters, clustering applications, SAN switches and directors, refer to the DS3000 series Interoperability Matrix available at ibm.com/systems/storage/disk/ ds3000/ds3400/ |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

For more information

Contact your IBM representative or
IBM Business Partner or visit:

- ibm.com/systems/storage/disk
- ibm.com/systems/x
- ibm.com/systems/bladecenter

© Copyright IBM Corporation 2008

IBM Systems and Technology Group
Route 100
Somers, NY 10589

Produced in the United States of America
February 2008
All Rights Reserved

IBM, the IBM logo, ibm.com, BladeCenter, Express Portfolio, FlashCopy, System Storage, System x and System p are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both. If these and other IBM trademarked terms are marked on their first occurrence in this information with a trademark symbol (® or ™), these symbols indicate U.S. registered or common law trademarks owned by IBM at the time this information was published. Such trademarks may also be registered or common law trademarks in other countries. A current list of IBM trademarks is available on the Web at "Copyright and trademark information" at ibm.com/legal/copytrade.shtml

Other company, product and service names may be trademarks or service marks of others.

This publication could include technical inaccuracies or typographical errors. This publication was produced in the United States. IBM may not offer the products, services or features discussed in this document in other countries, and the information may be subject to change without notice. Consult your local IBM business contact for information on the product or services available in your area.

All statements regarding IBM's future direction and intent are subject to change or withdrawal without notice and represent goals and objectives only.

Information about non-IBM products is obtained from the manufacturers of those products or their published announcements. IBM has not tested those products and cannot confirm the performance, compatibility, or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

MB, GB and TB = 1,000,000, 1,000,000,000 and 1,000,000,000,000 bytes, respectively, when referring to storage capacity. Accessible capacity is less; up to 3 GB is used in service partition. Actual storage capacity will vary based upon many factors and may be less than stated. Some numbers given for storage capacities give capacity in native mode followed by capacity using data compression technology. Maximum internal hard disk and memory capacities may require the replacement of any standard hard drives and/or memory and the population of all hard disk bays and memory slots with the largest currently supported drives available.

¹ IBM hardware products are made from new parts, or new and serviceable used parts. Regardless, our warranty terms apply. For a copy of applicable product warranties, write to: Warranty Information, P.O. Box 12195, RTP, NC 27709, Attn: Dept. JDJA/B203. IBM makes no representation or warranty regarding third-party products or services including those designated as ServerProven® or ClusterProven®



Recyclable, please recycle.

TSD03007-USEN-07